

PL-6KDTX



VIMET CORP

H64 Dương Thị Giang, P. Tân Thới Nhất, Quận 12, Tp HCM
Tel: 028 38 38 38 88 - 035 247 2468

Parking Lifts
SKU# 5175212
12,000-lb. Cap. Parking Lift / Tandem / Independent Platforms
Extra-Wide

Extra-Wide Superstructure Tandem-Platform Parking Lift

For wide-clearance vehicles, we've made the columns of the PL-6KDTX [parking lift](#) a little wider. This ensures that truck mirrors gracefully pass through the lift structure, and vehicle doors have a little more room to open and close. Some folks find the extra space more accommodating when they need to access the vehicle.

This lift is intended for use by anyone with four vehicles and a wide garage area to store them. You'll be surprised to see how well this unit fits in a variety of garage sizes. In the right space, it can be successfully utilized for commercial or residential purposes.

Features

- 6,000-lb. capacity per deck
- Perfect for cars, light trucks, motorcycles and ATVs
- Rugged I-beam and C-channel construction
- Built-in wheel stops
- Wide base-plate for maximum stability
- Front and rear wheel chocks
- Superstructure features durable powder-coat finish
- Dual hydraulic cylinders with heavy-duty steel lifting cable
- Heavy-duty steel construction
- Reliable electric-hydraulic power system
- Full-width platform to keep bottom vehicles protected
- Simple controls
- Oversized sheave diameter reduces cable fatigue
- High-speed lifting
- Features heavy-duty 3/8" aircraft cable
- Rugged 1.25" roller axles
- Multi-position safety locks in each column
- Runways feature non-skid surface
- Push-button pneumatic safety release
- Independent backup slack-cable safety latches
- Customizable power unit location



Specifications

Lifting Capacity 6,000 lbs. (2,722 kg)

Overall Width 250" (6,350 mm)

Overall Length 236.5" (6,008 mm)

Overall Height 123.75" (3,140 mm)

Min. Runway Height 9" (230 mm)

Max. Rise 89" (2,261 mm)

Width Between Posts 225" (5,713 mm)

Platform Width 82" (2,086 mm)

Platform Length 152" (3,862 mm)

Drive-thru Clearance 93" (2,374 mm)

Locking Positions 1 (Adjustable)

Lifting Time 30 sec

Standard Motor 220 VAC / 60 Hz / 1Ph

*Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.